



Heliport Controller Main unit

- * Cabinet RAL coated
- * Build in timer
- * TLOF 2 circuit @ 24VDC w/fail detection & dimming option
- * FATO 2 circuit @ 24VDC w/fail detection & dimming option
- * ADI 1 circuit @ 24 VDC w/fail detection & dimming option
- * Floodlight 1 circuit @ 230 Vac
- * WDI 230 1 circuit @ 230 Vac
- * Beacon, external or build-in
- * PLC Incl. Display and Touchpanel on front
- * Input power 230 Vac

Heliport Controller SMS Option:

NOTE: GSM card must configured to NO PIN code.

Control via SMS:

- * Send SMS to controller for full control over all Heliport Lights.
- * Turn on and off lights in individual group.
- * 4 output - 8 input
- * Receive status back on SMS
- * Send error message on SMS to Pilot or SMS/e-mail to maintenance
- * Individual programming



SMS module
2G/3G/4G Mobile band



Heliport Controller Radio Option:

- * Control Heliport Lights via Helicopter Radio
- * 3 click, 5 click or 7 click on radio will give 3 signal input to main controller
- * No feedback from controller

Heliport Cloud Option:

- * Full control & monitoring of Heliport via cell-phone, tablet or computer.
- * SMS and E-mail feedback
- * Connection to clients CMS
- * Meteorology system available as option

